



**PART # 74145**  
**Thru-Panel Battery Connector**


**NOTE:** Fits any firewall or panel up to 5/16" thick where a battery cable must pass through.

Parts List

(1) - Connector with Mounting Hardware

INSTALLATION INSTRUCTIONS

1. Select suitable mounting location with flat surface.
2. Cut hole as shown below. Begin with a 1-1/8" hole and use a file to shape.
3. Install Battery Connector and secure with supplied lock-nut.
4. Complete installation using high-amperage Battery Cable lock-nut. kits such as Moroso No. 74005, 74006 or 74055 Battery Cable Terminals No. 74175.



For Technical Assistance, Call Moroso's Tech Line

at

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

**MOROSO PERFORMANCE PRODUCTS, INC**  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At [www.moroso.com](http://www.moroso.com)

Rev.A  
030907

74145INST



**PART # 74145**  
**Thru-Panel Battery Connector**


**NOTE:** Fits any firewall or panel up to 5/16" thick where a battery cable must pass through.

Parts List

(1) - Connector with Mounting Hardware

INSTALLATION INSTRUCTIONS

1. Select suitable mounting location with flat surface.
2. Cut hole as shown below. Begin with a 1-1/8" hole and use a file to shape.
3. Install Battery Connector and secure with supplied lock-nut.
4. Complete installation using high-amperage Battery Cable lock-nut. kits such as Moroso No. 74005, 74006 or 74055 Battery Cable Terminals No. 74175.



For Technical Assistance, Call Moroso's Tech Line

at

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

**MOROSO PERFORMANCE PRODUCTS, INC**  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At [www.moroso.com](http://www.moroso.com)

Rev.A  
030907

74145INST



**PART # 74145**  
**Thru-Panel Battery Connector**


**NOTE:** Fits any firewall or panel up to 5/16" thick where a battery cable must pass through.

Parts List

(1) - Connector with Mounting Hardware

INSTALLATION INSTRUCTIONS

1. Select suitable mounting location with flat surface.
2. Cut hole as shown below. Begin with a 1-1/8" hole and use a file to shape.
3. Install Battery Connector and secure with supplied lock-nut.
4. Complete installation using high-amperage Battery Cable lock-nut. kits such as Moroso No. 74005, 74006 or 74055 Battery Cable Terminals No. 74175.



For Technical Assistance, Call Moroso's Tech Line

at

(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

**MOROSO PERFORMANCE PRODUCTS, INC**  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At [www.moroso.com](http://www.moroso.com)

Rev.A  
030907

74145INST