

Drive Shaft Safety Loop Mustang 2005-UP Part# C3160 / C3163

Parts List

- (1) Drive Shaft Loop Assembly
- (4) 3/8IN.X 1-1/4IN. Bolts
- (4) 3/8IN. Washer
- (4) LG Washers

- (1) Drive Shaft Loop Top
- (4) 3/8IN Nyloc Nuts
- (4) 12MM X 55MM Bolts
- (2) Push-in Pipe Plugs

<u>Installation instructions</u>

- Place the transmission in neutral and hoist the vehicle into position.
 While the vehicle is in the air, using a suitable transmission jack, support the transmission.
- 2. Remove the crossmember bolts.
- 3. Place the drive shaft Hoop on top of the existing crossmember and line up the bolt holes.
- 4. Replace the crossmember mounting hardware with the new (longer) mounting hardware included in this kit.
- 5. Place the push-in Plastic Tube Ends into the Drive Shaft Loop Assembly.
- 6. Torque the (4) Mounting bolts to 46lb-ft (Ford Motor Company Workshop Manual).
- 7. Position the Upper Retaining Hoop, completing the hoop assembly.
- 8. Install retaining hardware Bolts, Washers and Nyloc Nuts.

NOTE: Nyloc Nuts to the outside of the hoop.

- 9. Inspect the area around the drive shaft to ensure there are no obstructions.
- 10. Lower the vehicle and road test.

For Technical Assistance, call Competition Engineering's Tech Line at (203) 458-0542,(203) 458 0546 8:30am-5:00pm Eastern Time

COMPETITION ENGINEERING

80 Carter Drive • Guilford, CT 06437

Phone: (203) 453-5200 • Fax: (203) 453-6906

Visit Us At www.competitionengineering.com

Rev.B 021011 C3160INST