

Material Safety Data Sheet

COMPANY INFORMATION AND PRODUCT DESCRIPTION

Champion Brands LLC 1001 Golden Drive Clinton, MO 64735 P: 1-800-821-5693 www.championbrands.com	Product Name:	Sprint Wax
	Part Number	
	Revised Date:	3-10-14

INGREDIENTS INFORMATION/COMPOSITION

Chemical Name	CAS Number	Balance
Water	CAS# 7732-18-5	<3%
Methyl Alcohol	CAS# 67-56-1	5-8%
Polydimethylsiloxane Blend	CAS# 63148-62-9	<2%
Sodium Alkyl Napthtalene Sulfate	CAS# 6021-11-06	<1%
Coconut Oil Diehanolamide Cocoamide DEA	CAS# 8051-30-7	<1%

PHYSICAL AND CHEMICAL PROPERTIES

Specific Physical Form:	Liquid	Solubility in Water	@ 25 C 0.865
Odor, Color, Grade	Light White	pH	Yes
Boiling Point	>95 C	Flash Point	6-7.5
Physical Appearance	Light White Liquid	Viscosity	195 degrees F
Percent Volatiles	<3%	Flammability	145 mm2/s
Evaporation rate	NA	Oxidation Properties	None
Explosive Properties	None	Oxidation Properties	None

HAZARDS AND FIRST AID MEASURES

Skin:	Flush exposed area with water. Remove all contaminated clothing. Prolonged or repeated contact can cause moderate irritation.
Breathing:	Excessive inhalation can cause nasal and respiratory irritation and or damage, dizziness, nausea, headache, and possible unconsciousness.
Eyes:	Flood with large amounts water at least 20 min.; get immediate medical attention if irritation persists. Can cause severe irritation, redness, tearing, and blurred vision.
Inhalation:	If affected, remove individual to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration. Keep person warm, calm, and get medical attention. Treat same as methyl alcohol poisoning.
Swallowing:	Can Cause, nausea, vomiting, and diarrhea. Do not induce vomiting. Aspiration of liquid while vomiting may injure lungs seriously. Overexposure by ingestion may cause drowsiness, dizziness or confusion. Seek Medical Attention immediately Product generates methyl alcohol which may cause blindness and possibly death if swallowed.

FIRE FIGHTING MEASURES

Firefighting Procedure. Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals. Evacuate area in case of overheating or fire. Vapors are heavier than air and may travel to a source of ignition and flash back. Static electricity will accumulate and may ignite vapors. Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide. Nitrogen oxides. Formaldehyde.

PERSONAL PROTECTION

Health 0	Flammability 0	Reactivity 0
<p>Respiratory Protection: If workplace exposure limits of the product or any component are exceeded, a NIOSH/MSHA respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirator (negative pressure type) under specific conditions. (See your industrial hygienist) Engineering of administrative controls should be implemented to reduce exposure.</p> <p>Ventilation : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s).Protective</p> <p>Gloves: Wear resistant gloves. (Consult your safety equipment supplier).</p> <p>Eye Protection: Compliance with OSHA regulations is advised.</p> <p>Other Protective Equipment: To prevent skin contact, wear impervious clothing.</p>		

STABILITY AND REACTIVITY			
Stability	Stable	Materials and conditions to Avoid	Avoid contact with strong oxidizing agents.
Hazardous Polymerization:	Cannot occur		
Hazardous Decomposition:	None		
TRANSPORTATION INFORMATION			
No special shipping requirements		Keep away from food stuffs	
DISPOSAL CONSIDERATIONS			
Waste Disposal Method: Dispose of in accordance with all local, state, and federal regulations			
SPILL OR LEAK PROCEDURES			
If Spilled or Leaked: Shut off ignitions sources. Stop spill at source, contain spill and keep from entering waterways or sewers. Small quantities may be soaked up on inert absorbents.			
SPECIAL PRECAUTIONS AND OTHER COMMENTS			
<p>Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.</p> <p>TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA inventory of chemical substances.</p> <p>EPA SARA Title III chemical listings. Section 302 Extremely hazardous substances: None Section 304 CERCLA hazardous substances: None Section 312 hazard class: Acute: Yes Chronic: Yes Fire: No Pressure: No Reactive: No Section 313 toxic chemicals: Methyl alcohol (67-56-1) < 3% by Wt. Supplemental State Compliance Information.</p>			