



**Oil Restrictor Kit
PART #20000**

WARNING: Do NOT use with hydraulic lifters

INSTALLATION INSTRUCTIONS

Installs into cam journal.

Parts List

2- 5/16"-18 restrictors with .060" orifice dia.

1. Remove freeze plug and camshaft bearing.
2. Tap the two oil gallery holes to accept the 5/16"-18 plugs and remove all metal chips.
3. Apply red Loctite® to restrictor threads and install.
4. Replace bearing and freeze plug.

Note: The .060" pre-drilled orifice is suitable for most wet/dry oiling systems. If your engine setup requires greater oil flow, simply enlarge (drill) the orifice in each plug.



**Oil Restrictor Kit
PART #20000**

WARNING: Do NOT use with hydraulic lifters

INSTALLATION INSTRUCTIONS

Installs into cam journal.

Parts List

2- 5/16"-18 restrictors with .060" orifice dia.

1. Remove freeze plug and camshaft bearing.
2. Tap the two oil gallery holes to accept the 5/16"-18 plugs and remove all metal chips.
3. Apply red Loctite® to restrictor threads and install.
4. Replace bearing and freeze plug.

Note: The .060" pre-drilled orifice is suitable for most wet/dry oiling systems. If your engine setup requires greater oil flow, simply enlarge (drill) the orifice in each plug.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

22000INST

Rev.A
062107

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

22000INST

Rev.A
062107



**Oil Restrictor Kit
PART #20000**

WARNING: Do NOT use with hydraulic lifters

INSTALLATION INSTRUCTIONS

Installs into cam journal.

Parts List

2- 5/16"-18 restrictors with .060" orifice dia.

1. Remove freeze plug and camshaft bearing.
2. Tap the two oil gallery holes to accept the 5/16"-18 plugs and remove all metal chips.
3. Apply red Loctite® to restrictor threads and install.
4. Replace bearing and freeze plug.

Note: The .060" pre-drilled orifice is suitable for most wet/dry oiling systems. If your engine setup requires greater oil flow, simply enlarge (drill) the orifice in each plug.



**Oil Restrictor Kit
PART #20000**

WARNING: Do NOT use with hydraulic lifters

INSTALLATION INSTRUCTIONS

Installs into cam journal.

Parts List

2- 5/16"-18 restrictors with .060" orifice dia.

1. Remove freeze plug and camshaft bearing.
2. Tap the two oil gallery holes to accept the 5/16"-18 plugs and remove all metal chips.
3. Apply red Loctite® to restrictor threads and install.
4. Replace bearing and freeze plug.

Note: The .060" pre-drilled orifice is suitable for most wet/dry oiling systems. If your engine setup requires greater oil flow, simply enlarge (drill) the orifice in each plug.

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

22000INST

Rev.A
062007

**For Technical Assistance, Call Moroso's Tech Line at
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Visit Us At www.moroso.com

22000INST

Rev.A
062107