



Toll Free: 800-788-9353 Sales Direct: 816-423-5728 Email: info@weldracing.com

CADILLAC

This fitment guide applies to vehicles with O.E. suspension, wheel wells, and brakes unless otherwise noted.

Other S71 & S74 sizes and offsets are available, please call the Sales and Tech Department for more information at 800-788-9353

Vehicle		Wheel Style	Pad Height	Size	Vehicle Location	Weld Offset	Weld B/S	Partial Part Number fill in the X = style # (1 or 4) and Y = center finish (B or P)	Notes
2009+ CTS-V	17"	S71	High	17x5.0	Front	-21	2.20	71Hy7050N22A	Front wheel application requires 3/16" spacer & will exceed fender by 3/8"
		S71	High	17X7.0	Front	5	4.20	71Hy7070N42A	Front wheel application requires 3/16" spacer & will exceed fender by 3/8"
		S71	High	17X8.0	Front & Rear	18	5.20	71Hy7080N52A	Front wheel application requires 3/16" spacer & will exceed fender by 3/8"
		S71	High	17x9.0	Front & Rear	31	6.20	71Hy7090N62A	Front wheel application requires 3/16" spacer & will exceed fender by 3/8"
		S71	High	17x10.0	Rear only	44	7.20	71Hy7100N72A	Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors
	18"	S71+S74	High	18x5.0	Front	-23	2.10	7xHy8050N21A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	18x7.0	Front	3	4.10	7xHy8070N41A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	18x8.0	Front & Rear	15	5.10	7xHy8080N51A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	18x9.0	Front & Rear	28	6.10	7xHy8090N61A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	18x10.0	Rear only	41	7.10	7xHy8100N71A	Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors
		S71+S74	High	18x10.5	Rear only	47	7.60	7xHy8105N76A	Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors
	20"	S71+S74	High	20x5.0	Front	-20	2.20	7xHy0050N22A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	20x7.0	Front	5	4.20	7xHy0070N42A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	20x8.0	Front & Rear	18	5.20	7xHy0080N52A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	20x9.0	Front & Rear	31	6.20	7xHy0090N62A	Front wheel application will exceed fender by 3/16"
		S71+S74	High	20x10.0	Rear only	43	7.20	7xHy0100N72A	Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors
		S71+S74	High	20x10.5	Rear only	50	7.70	7xHy0105N77A	Front/Rear tire heights must be within 1/2" of each other to prevent traction control errors

This fitment guide applies to vehicles with O.E. suspension, wheel wells, and brakes unless otherwise noted.