




74103/74104

Battery Terminal Disconnect Switch

INSTALLATION INSTRUCTIONS

NOTE: Disconnects Battery Power with one counter-clockwise turn of the knob. **Do not** attempt to pull the Two halves of this assembly apart.

1. Remove Negative cable from bat.
2. Clean Bat. Neg. post/side post, with wire brush.
3. Install Bat. Terminal Disconnect Switch onto Neg. post/ Neg. side post.
4. Install Bat. ground cable onto Bat. Terminal Disconnect Switch.



For Technical Assistance, Call Moroso's Tech Line at (203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
030207

Visit Us At www.moroso.com

74103INST




74103/74104

Battery Terminal Disconnect Switch

INSTALLATION INSTRUCTIONS

NOTE: Disconnects Battery Power with one counter-clockwise turn of the knob. **Do not** attempt to pull the Two halves of this assembly apart.

1. Remove Negative cable from bat.
2. Clean Bat. Neg. post/side post, with wire brush
3. Install Bat. Terminal Disconnect Switch onto Neg. post/ Neg. side post.
4. Install Bat. ground cable onto Bat. Terminal Disconnect Switch.



For Technical Assistance, Call Moroso's Tech Line at (203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
030207

Visit Us At www.moroso.com

74103INST




74103/74104

Battery Terminal Disconnect Switch

INSTALLATION INSTRUCTIONS

NOTE: Disconnects Battery Power with one counter-clockwise turn of the knob. **Do not** attempt to pull the Two halves of this assembly apart.

1. Remove Negative cable from bat.
2. Clean Bat. Neg. post/side post, with wire brush
3. Install Bat. Terminal Disconnect Switch onto Neg. post/ Neg. side post.
4. Install Bat. ground cable onto Bat. Terminal Disconnect Switch.



For Technical Assistance, Call Moroso's Tech Line at (203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
030207

Visit Us At www.moroso.com

74103INST




74103/74104

Battery Terminal Disconnect Switch

INSTALLATION INSTRUCTIONS

NOTE: Disconnects Battery Power with one counter-clockwise turn of the knob. **Do not** attempt to pull the Two halves of this assembly apart.

1. Remove Negative cable from bat.
2. Clean Bat. Neg. post/side post, with wire brush
3. Install Bat. Terminal Disconnect Switch onto Neg. post/ Neg. side post.
4. Install Bat. ground cable onto Bat. Terminal Disconnect Switch.



For Technical Assistance, Call Moroso's Tech Line at (203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time

MOROSO PERFORMANCE PRODUCTS, INC
80 CARTER DR • GUILFORD, CT 06437
Phone: (203) 453-6571 • Fax: (203) 453-6906

Rev.A
030207

Visit Us At www.moroso.com

74103INST